## LISTING OF THE CLAIMS

This listing of the claims will replace all prior versions and listings of claims in the application.

- 1-99. (Cancelled).
- 100. (Previously Presented) A five layer stitchless seam comprising a first thermoplastic tape portion, a first substrate portion in contact with said first thermoplastic tape portion, a second thermoplastic tape portion in contact with said second thermoplastic tape portion, and a third thermoplastic tape portion in contact with said second substrate portion to provide a flexible stitchless seam between the five layers, wherein at least one of said first thermoplastic tape portion, said second thermoplastic tape portion, and said third thermoplastic tape portion is a multi-layer tape portion that runs the length of the seam and includes a first continuous layer having a first melting point and a second continuous layer having a second melting point.
- 101. (Previously Presented) The seam of claim 100, wherein at least two of the tape portions are contiguous.
  - 102. (Cancelled).
- 103. (Previously Presented) The seam of claim 100, wherein at least two of said tape portions and said substrate portions are the same materials.
- 104. (Previously Presented) The seam of claim 100, wherein the first substrate portion and the second substrate portion are different materials.

- 105. (Previously Presented) The seam of claim 100, wherein at least one of the substrate portions comprises a barrier layer.
- 106. (Previously Presented) The seam of claim 105, wherein at least one of the substrate portions comprises a fabric.
- 107. (Previously Presented) The seam of claim 105, wherein both the first substrate portion and the second substrate portion comprise a fabric.
- 108. (Previously Presented) The seam of claim 100, wherein at least four areas of the first and second substrate portions are bonded in a cross-sectional area of the seam and wherein the seam has a strength greater than a double felled needle sewn seam made with the same substrates.
- 109. (Previously Presented) The seam of claim 100, wherein at least four areas of the first and second substrate portions are bonded in a cross-sectional area of the seam and wherein the tensile grab strength is at least about 85kg.
- 110. (Previously Presented) The seam of claim 100, wherein the tensile grab strength is at least about 114 kg.
- 111. (Previously Presented) The seam of claim 100, wherein the tensile grab strength is at least 135 about kg.
- 112. (Previously Presented) The seam of claim 100, wherein the tensile grab strength is at least about 150 kg.
- 113. (Previously Presented) The seam of claim 100, wherein the seam is a welded seam.
  - 114-122. (Cancelled).

- 123. (Currently Amended) A multilayer stitchless seam comprising a first tape portion, a first substrate portion in contact with said first tape portion, a second tape portion in contact with said first substrate portion, a second substrate portion in contact with said second tape portion, [[and]] a third tape portion in contact with said second substrate portion to provide a flexible seam between the layers, and a third substrate portion, wherein at least one of the first substrate and the second substrate is a composite substrate comprising at least two layers.
  - 124. (Cancelled).
  - 125. (Cancelled).